

AquaFlow

Unvented single coil water cylinder

WRAS APPROVED

ANTI CORROSION

HIGH PERFORMANCE



AquaFlow

Unvented single coil water cylinder



Inner shell guaranteed for 25 years, made from Super-Molybdenum.

2 years guarantee on ancillary components.

High performance mains pressure to all hot water outlets.

Up to 50-litre per minute flow rate.

WRAS Approved.

Fully flooded expansion facility enabling storage capacity from 125 – 250 litres from the 3 model range.

No need for 'sacrificial anode' due to excellent anti-corrosion properties of Super-Molybdenum.

Compact dimensions.

3kW immersion heater and energy cut-out device supplied as standard.

Optional secondary return connection if required.

Thermal insulation and energy efficient coil meet Part L Requirements.



| SPECIFICATIONS | AquaFlow 150 | AquaFlow 200 | AquaFlow 300 |
|--------------------------|--------------|--------------|--------------|
| Capacity range (L) | 125-150 | 170-200 | 210-250 |
| Height (mm) | 900mm | 1150mm | 1400mm |
| Depth (diameter) | 580mm | 580mm | 580mm |
| Weight (when full) | 190kg | 240kg | 300kg |
| Coil rating | 12kW | 26.5kW | 26.5kW |
| Average recovery time | 30 min | 26 min | 28 min |
| Energy loss (kW/day) | 1.78 | 2.04 | 2.45 |
| Maximum working pressure | 8-bar | 8-bar | 8-bar |



Registered Address: Vokera Ltd Borderlake House, Unit 7 Riverside Industrial Estate, London Colney, AL2 1HG

Email: enquiries@vokera.co.uk Web: www.vokera.co.uk
 Vokera Ireland West Court, Callan, Co Kilkenny

Tel: 0844 391 0999 Fax: 0844 391 0998
 Tel: 056 7755057 Fax: 056 7755060

Vokera is a licensed member of the Benchmark scheme which aims to improve the standards of installation and commissioning of domestic hot water systems in the UK.